

HDMI UTP Extender HDMI Extender

Model: PW-DT237P-IR

USER MANUAL

1.Description

The H.264 HDMI extender adopts standard Ethernet TCP/IP protocol, transmit HD video and audio over single cat6 cable, and support One-to-many applications with POE switches. The equipment has excellent image processing and transmission capacity, makes signal transmission more smooth and steady, is a kind of economic and efficient way of HDMI signal extension.

2.Features

- Transmits HDMI video and audio signals up to 150m over a single CAT6 cable;
- Support video resolution up to 1920*1080P@60Hz;
- Supports over TCP/IP protocol, One-to-many applications with POE switches;
- Supports for external IR expansion;
- Support over TCP/IP;
- Compliance with HDMI 1.3 and HDCP 1.2 standard;
- High compatibility, can auto-match source and display device;
- Built-in automatic adjustment system, make the image smooth, clear and stable;
- Simple to install, plug and play.

3.Package list





① HDMI transmitter	1 pcs
② HDMI receiver	1 pcs
③ Power adapter	2 pcs
④ IR transmitter/receive cable	1 pcs
⑤ User manual	1 pcs

4.Specifications



Parameter	Description	
Video	Standards	HDMI 1.3;HDCP1.3
	Compressed format	H.264
	Maximum pixel clock	165MHz
	Maximum data rate	6.75Gbps
	Resolution	1920X1080P@60Hz
	Connector	HDMI-A
Impedance	100Ω	
IR	Interface	3.5mm earphone seat
	Signal direction	Unidirectional
	Signal type	Digital
UTP	IR frequency	20-60kHz
	Interface	RJ45
Other	Transmission distance	CAT6---150m CAT5E---150m
	Power supply	The power adapter: DC 12V POE input voltage range:36~57V
	Power dissipation	MAX 3.3W
	Temperature	Operating: -5°C ~ +70°C
	Humidity	Operating: 5% ~ 90%
	Dimension	94*71*26mm
The warranty	1 year free warranty	

5.Panel

Transmitter:




Receiver:



Port name	Description
HDIN/HDOUT	HD signal input/output
UTP	RJ45 port connect cat5E/6
IR IN/IR OUT	IR input/IR output
RESET	System reset button, press 5 seconds
DC5-12V	Power adapter socket
LED indicator	Description
PWR	System power indicator
STA	Video signal indicator

6.Diagram



① DVD ② monitor ③ Transmitter ④ receiving end

⑤ monitor ⑥ remote control

7.Warranty

Thank you very much for using our products.

The warranty time is one year and life-long maintenance. During this period, any belongs to under normal usage circumstance cause because of the product quality's problem of breakdown, our company will be responsible for giving free maintain.

▲ Safety instruction

- 1.The malfunction and damaged caused by incorrect use, the unauthorized repairs and alteration;.
- 2.The damage caused by fire, flood, abnormal voltage, other natural disasters and secondary product damage;.
- 3.The product malfunction caused by not in accordance with the user manual operation;.
- 4.The malfunction and damaged caused by the other barriers (man-made factors or external device).

If you need after-sales service, please contact us directly, and provide complete warranty card and purchase note.

www.pwaytek.com

Shenzhen Pinwei Technology Co.,Ltd.

Tel: +86(0)755 83240274

Official Website:www.pwaytek.com

Address: 6/Floor, No.21, Tianxi Road, Longhua District, Shenzhen, Guangdong, China. ZIP:51